

The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof

Project		Date	
Part		Type	



About The Vauxhall Series

The BLHV-H27 is a high bay LED hazardous location fixture. The BLHV-H27 is ideal for indoor or outdoor use where there is a high probability of exposure to hazardous dust or gases. Its unique, IP67 certified body makes it ideal in environments where vapour-proof efficiency an performance are a factor.

Specifications

Supported Voltage	120-277V, 347V, 480V
Available Sizes	2', 4'
Lifetime	L70 of 136,000+ hours, L90 of 38,000+ hours
Lumens	2' 10L (10000lm) to 4' 32L (32000lm).
Operating Temperature	-20°C/+35°C (-40°/+55°C upgrade)
CCT	2700K, 3000K, 3500K, 4000K, 5000K, 6500K
CRI	80+ standard, 90+ and 95+ available
Dimming	0-10V Standard
Mounting	Hooks provided for suspension mounting; Surface-mount brackets available;

Approvals

- NSF Rated
- IP67 Rated
- NEMA4X Rated
- ETL Listed
- DLC Listed
- Class 1 Div 2 Groups ABCD
- Class 2 Div 2 Groups FG
- Class 3 Div 2
- Designed and Manufactured in Canada

Warranty

- 5 Year Comprehensive, 10 Year LED

The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof

Vapour-Proof Lighting by



Ordering Information

Fill in the fields below with your product selections. If you need help with this section, [contact your local sales professional](#).

Length CRI & Colour Temperature Option 1
BLHV-H - 2' - 20L - 840 - UNV - H27
Fixture Series Lumen Output Voltage

1	2	3	4	5						
BLHV-H										
Series	Length & Lumen Output				CRI	CCT	Voltage			
BLHV-H	2'- 10L	10000 lm	2'- 18L	18000 lm	8	80	27	2700K	UNV	120-277V
	2'- 12L	12000 lm	2'- 20L	20000 lm	9	90+	30	3000K	347	347V
	2'- 14L	14000 lm	4'- 24L	24000 lm	1	95+	35	3500K	480	480V
	2'- 16L	16000 lm	4'- 32L	32000 lm			40	4000K		
							50	5000K		
							65	6500K		
6										

Options

Hazardous Location

H27 Hazardous Location

Applied Certifications

Class 1 Div 2 Groups ABCD

Class 2 Div 2 Groups FG

Class 3 Div 2

Lenses

L26 Clear Polycarbonate Lens

L49 Frosted Acrylic Lens

L55 Clear Acrylic Lens

L59 Frosted Polycarbonate Lens

Cords

W1xx White 16/4 (Specify Length)

W2xx Black 16/4 (Specify Length)

W3xx White 16/3 (Specify Length)

W4xx Black 16/3 (Specify Length)

W*** Other Options Available*

Key.	Cord Length.	Key	Cord Length
6	6FT	15	15FT
10	10FT	20	20FT

Ex. **W406** would be 16/3 Black, 6FT

Dimming

B11 0-10V Dimming Leads

Packaging

BLANK Individually Boxed on Pallets

P0 Bulk Packaging

Fasteners

BLANK Stainless Steel Latches and Clips

Mounting

M3xx Y-Toggle Aircraft Cables

M14 Heavy Duty Surface Mount Brackets

M20 Ceiling-Mount V-Hooks

Key.	Aircraft Length.	Key	Aircraft Length
5	5FT	15	15FT
10	10FT	20	20FT

Ex. **M305** would be Y-Toggle, 5FT

Warranty

CL7 10-Year Comprehensive Warranty Upgrade

The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof

Vapour-Proof Lighting by



Certifications and Listings

Certifications that apply to this fixture and its possible configurations are listed here. More information available upon request.

Icon	Description
	DLC Listed
	ETL Listed
	NEMA4X Rated
	IP67 Rated
	NSF Rated
	90 and 95+ CRI Options Available
	-40C Option Available
	Hazardous Location Ready

Usage Applications

This fixture can be used in a variety of applications, and is ideal for the following:

Usage Application
Hazardous Location
Agricultural Barns
Cold Storage & Freezers
Distribution Facilities
Food Processing Plants
Grocery Stores
Logistics & Warehousing
Manufacturing Facilities
Outdoor Parking Structures
Processing Plants
Storage Facilities
Wash Bays & Wet Environments

Warranty Statement

BJ Take products are tested and/or inspected prior to being packaged for shipment and are guaranteed from the day the product is shipped for a period of ten-year LED chip warranty and a five-year comprehensive component warranty. This can be upgraded to a ten-year comprehensive warranty on request.


The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof


Vapour-Proof Lighting by

BJTAKE
LIGHTING


BLHV-H27 2' Side




BLHV-H27 2' End



BLHV-H27 4' Side



BLHV-H27 4' End



BLHV-H27 2' Wattage

Length	Size	Lumen Output	Fixture Wattage	Lumens per watt
2'	10	10208	69.21	147.5
2'	12	11768	80.43	146.3
2'	14	13334	91.88	145.1
2'	16	14874	103.33	143.9
2'	18	16820	116.52	144.4
2'	20	18772	129.71	144.7

BLHV-H27 4' Wattage

Length	Size	Lumen Output	Fixture Wattage	Lumens per watt
4'	24	22720	156.08	145.6
4'	32	29630	203.69	145.5

* Drawings aren't to scale


* Standard tolerances apply

* Specifications may change without notice

The Vauxhall Series


BLHV-H27 - Hazloc Vapour Proof

BLHV-H-2FT-12L-840-L49-H27



Mtg Height	Light Level	Beam Diameter
6.0 ft	108.5 fc	17.7 ft
8.0 ft	61.0 fc	23.6 ft
10.0 ft	39.0 fc	29.5 ft
12.0 ft	27.1 fc	35.4 ft
14.0 ft	19.9 fc	41.3 ft
16.0 ft	15.3 fc	47.2 ft
24.0 ft	6.8 fc	70.8 ft
32.0 ft	3.8 fc	94.4 ft
40.0 ft	2.4 fc	118.0 ft
48.0 ft	1.7 fc	141.7 ft
56.0 ft	1.2 fc	165.3 ft
64.0 ft	1.0 fc	188.9 ft

BLHV-H-2FT-16L-840-L49-H27




Mtg Height	Light Level	Beam Diameter
6.0 ft	147.5 fc	17.5 ft
8.0 ft	82.9 fc	23.3 ft
10.0 ft	53.1 fc	29.1 ft
12.0 ft	36.9 fc	34.9 ft
14.0 ft	27.1 fc	40.7 ft
16.0 ft	20.7 fc	46.6 ft
24.0 ft	9.2 fc	69.8 ft
32.0 ft	5.2 fc	93.1 ft
40.0 ft	3.3 fc	116.4 ft
48.0 ft	2.3 fc	139.7 ft
56.0 ft	1.7 fc	162.9 ft
64.0 ft	1.3 fc	186.2 ft

The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof

BLHV-H-2FT-20L-840-L49-H27



Mtg Height	Light Level	Beam Diameter
6.0 ft	179.3 fc	18.0 ft
8.0 ft	100.9 fc	24.0 ft
10.0 ft	64.6 fc	30.0 ft
12.0 ft	44.8 fc	36.0 ft
14.0 ft	32.9 fc	42.1 ft
16.0 ft	25.2 fc	48.1 ft
24.0 ft	11.2 fc	72.1 ft
32.0 ft	6.3 fc	96.1 ft
40.0 ft	4.0 fc	120.2 ft
48.0 ft	2.8 fc	144.2 ft
56.0 ft	2.1 fc	168.2 ft
64.0 ft	1.6 fc	192.3 ft

The Vauxhall Series

BLHV-H27 - Hazloc Vapour Proof

Vapour-Proof Lighting by **BJTAKE**
LIGHTING

Gallery Information

Below you will find images of relevant products and configurations for the BLHV-H27.

